



1615 - 2315

# 1615

The Macdonald 1615 Rock Drill is lightweight and compact and is therefore ideal for pop holing, for gas work and gives excellent service in confined spaces. It is designed for hand drilling holes suitable for blasting operations in mines and quarries and is capable of being used on rocks of varying hardness. The 1615 will drill a 34mm diameter hole up to 1.5 metres deep.

model	CHUCK SIZE		WEIGHT		LENGTH		BORE		STROKE		FRQ'CY		AIR CONS		REC.WRKG		AIR HOSE		HOSE FITTING
	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
1615	7/8	22	36	16	22	545	2.16	55	2	50	2200	37	86	41	90	6	3.4	19	3/4.NPT



# 2315

The Macdonald 2315 Rock Drill is a medium weight tool designed for drilling holes suitable for blasting operations in mines and quarries and is capable of being used on rock of varying hardness. The tool will drill a 45mm diameter hole up to 4 metres deep or 42mm diameter hole up to 6 metres deep.

model	CHUCK SIZE		WEIGHT		LENGTH		BORE		STROKE		FRQ'CY		AIR CONS		REC.WRKG		AIR HOSE		HOSE FITTING
	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
2315	7/8	22	51	23	28	720	2.75	70	2	50	2100	35	120	56	90	6	3/4	19	3/4.NPT
	1	28	51	23	28	720	2.75	70	2	50	2100	35	120	56	90	6	3/4	19	3/4.NPT



# STANDARD DRILLS COMPARISON SHEET

model	CHUCK SIZE		WEIGHT		LENGTH		BORE		STROKE		FRQ'CY		AIR CONS		REC.WRKG		AIR HOSE		HOSE FITTING
	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
1615	7/8	22	36	16	22	545	2.16	55	2	50	2200	37	86	41	90	6	3.4	19	3/4.NPT



1615

model	CHUCK SIZE		WEIGHT		LENGTH		BORE		STROKE		FRQ'CY		AIR CONS		REC.WRKG		AIR HOSE		HOSE FITTING
	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
2315	7/8	22	51	23	28	720	2.75	70	2	50	2100	35	120	56	90	6	3/4	19	3/4.NPT
	1	28	51	23	28	720	2.75	70	2	50	2100	35	120	56	90	6	3/4	19	3/4.NPT



2315

STANDARD DRILLS