

284S

BREAKER SPECIFICATION SHEET



MACDONALD

284S

The Macdonald range of standard breakers has been developed over many years with the design proven in construction & allied industries throughout the world.

Powerful and manoeuvrable, the Macdonald 284S pneumatic breaker has an excellent power to weight ratio. This makes it the ideal tool for a wide variety of heavy duty demolition & narrow trench work jobs.

BENEFITS

- Cushioned handle grips for operator comfort & productivity.
- Silencer for effective noise suppression.
- Well balanced, manoeuvrable & high strike energy.
- Quick change retainer.
- Ease of use due to swivel air connection.
- Easily maintained without specialist tools.
- Drop forged components for minimum wear & maximum life.
- Built in reservoir for automatic oiling & smooth continuous operation.
- Small number of moving parts to minimise internal wear.



SPECIFICATION

WEIGHT	32.5 KGS	AIR CONSUMPTION	65 CFM	
FREQUENCY	1250 BPM	LENGTH	650 MM	
CHUCK SIZE	WORKING PRESSURE	BORE	STROKE	AIR HOSE
32 or 28 MM	6 BAR 90 PSI	57 MM	146 MM	19 MM

For sales & enquiries call:
+44 (0) 1355 221215



Macdonald Air Products Ltd. Registration in Scotland No.366829

77 Carron Place, Kelvin Industrial Estate, East Kilbride, G75 0YL, Scotland
Email: info@macdonaldairtools.com | Web: macdonaldairtools.com