

24VRS

BREAKER SPECIFICATION SHEET



MACDONALD

24VRS


This Macdonald vibration reduced breaker will suit most light to medium breaking jobs on concrete, asphalt & footpaths.

Designed to withstand the demands of the plant hire industry, combined with light weight preferred by the utilities & local authorities.

The 24VRS strikes a balance between hard hitting performance & vibration reduced levels required by today's operators.

BENEFITS

- Ergonomic handles to reduce operator exposure to hand arm vibration.
- Cushioned grips for operator comfort & productivity.
- Silencer for effective noise suppression.
- Well balanced, manoeuvrable & good strike energy.
- Quick change retainer.
- Easily maintained without specialist tools.
- Drop forged components for minimum wear & maximum life.
- Built in reservoir for automatic oiling & smooth continuous operation.
- Small number of moving parts to minimise internal wear.



SPECIFICATION

| | | | | |
|--------------------|----------------------------|-----------------|------------------|--------------|
| WEIGHT | 26 KGS | AIR CONSUMPTION | 48 CFM | |
| VIBRATION | 6.4 MS ² | NOISE LEVEL | 108 DB(A) | |
| FREQUENCY | 1250 BPM | LENGTH | 700 MM | |
| CHUCK SIZE | WORKING PRESSURE | BORE | STROKE | AIR HOSE |
| 32 or 28 MM | 6 BAR 90 PSI | 57 MM | 127 MM | 19 MM |

For sales & enquiries call:
+44 (0) 1355 221215



Macdonald Air Products Ltd. Registration in Scotland No.366829

77 Carron Place, Kelvin Industrial Estate, East Kilbride, G75 0YL, Scotland
Email: info@macdonaldairtools.com | Web: macdonaldairtools.com